

Graphite Packing Reinforced with Metal Wire

Code: RGSP401



Rubber & Gasket Supplies Co., Ltd

Description

Corrosion inhibitor acts as a sacrificial anode to protect the valve stem and the stuffing box.



Item no.: RGSP401

Graphite Packing Reinforced with Metal Wire Item no.: RGSP401

Graphite packing reinforced with wire is braided from expanded graphite yarns, reinforced with metal wire, normally reinforced with inconel wire. It retains all the inherent benefits of SUNWELL P400 flexible graphite packing. The wire reinforcement provides greater mechanical strength, used for high pressure and temperatures.

Typical Application

- * Flexible graphite packing is a multi-service packing capable of a wide variety of uses throughout a plant.
- * It can be used in valves, pumps, expansion joints, mixers and agitators in high-pressure and temperature.
- * Excellent for use in steam turbines, high temperature motor-actuated valves
- * High temperature and high pressure valve applications in general.

Prime Features

- * It can be reinforced with nickel, stainless steel, copper, etc.
- * High pressure, high temperature
- * Wide variety of uses throughout a plant
- * Precaution: in oxidizing environment may use with anti-extrusion packing rings.

Technical Data

Material		100% Expanded Graphite (Metal mesh)
Temperature Range		-220 up to +555 oC atmosphere; -200 up to +650oC in Steam
Process	Fans	5 bar
	Agitators	15 bar
	Valves	30 bar
Shaft Speed		23 m/s in fans
PH		0~14
Density		1.5 g/cm3