Mineral Fiber Beater Sheet

Code: RGSB705



Description

Mineral Fiber beater sheet is made from synthetic latex, Mineral Fiber fiber and filling materials, normal used for automobile, agricultural machinery, etc.

RGSB705V -- Vulcanized Mineral Fiber latex sheet, it is by vulcanizing, it has smooth face and high density, it can be cut into all kinds of gaskets directly.



Item no.: RGSB705

Mineral Fiber Beater Sheet Item no.: RGSB705

* Suitable for sealing lubricating oil at highest temperature 200oC

Typical Application

- * Used for make gaskets.
- * Automobile, agricultural machinery, motorcycle, engineering machinery, etc
- * Suitable for lubricating oil under temperature 200oC.

Technical Data

Item	RGS Style	
	B705Mineral Fiber latex paper	B805V Vulcanized Mineral Fiber latex sheet
Density g/cm3	0.9~1.1	1.2~1.4
Tensile strength ≥ Mpa	2.5	5
Compressibility ≥ %	40+/-7	20+/-5
Recovery ≥ %	20	40
Stress relaxation ≤ %	30	30
In 20# aviation oil, 150oC,		
30min		
Oil absorption	≤ 50%	≤30%
Thickness increase	≤6%	≤12%
In water 15~30oC, 5h	≤6%	≤12%

Normal color: Grey, Black, White.

Item	Tolerance
Thickness	+/-mm
0.5	0.05
0.6~0.8	0.06
1~2	0.08

Copyright © 2014 RGS
Rubber & Gasket Supplies Co., Ltd
Rm 1811, Huaxia Media Buliding
No.53N. Avenue, Yantai, Shandong 264000 China
sales@rgs-asia.com

Mineral Fiber Beater Sheet

Rubber & Gasket Supplies Co., Ltd

Code: RGSB705 **Dimensions**

Thickness: 0.3~2.0mm

500x1500mm; 500x1000mm; 500x500mm; 500x1200mm; 1000x1500mm; 1000x1200mm;