Synthetic Fiber Beater Sheet

Code: RGSB103



Description

Synthetic Fiber beater sheets is a high performance medium density material for use as soft gasket manufactured from a blend of cellulose and aramid fibers combined with reinforced inorganic filler, imparts an excellent sealing at medium flange loads. It has good compressibility and coefficient of resilience. The inside can properly swell to meet oil which affected self-sealing.



Synthetic Fiber Beater Sheet Item no.: RGSB103

- * 100% not including asbestos
- * Wide range of temperatures
- * Meet oil can be affected self-sealing

Item no.: RGSB103

Typical Application

- * Suitable for automobile, farm machinery, motors, etc
- * It can be used in oil system and water supply system at temperature 150 deg.C

Technical Data

Item	Unit	B103	B103V
Density	G/cm3	0.9~1.1	1.2~1.4
Tensile strength	≥Mpa	12.7	
Compressibility	%	15+/-5	
Recovery	≥%	45	
Stress relaxation	≤%	35	
Weight increase (in oil)	≤%	35	
Thickness increase (in oil)	≤%	15	

Tolerance

Item	Tolerance	
Thickness	+/-mm	
0.5	0.05	
0.6~0.8	0.06	
1.0~2.0	0.08	

Color

Black, grey, etc. It can be produced following your requirements. With anti-stick (B103S), Graphite coating (B103G) Can put your logo on.

> Copyright © 2014 RGS Rubber & Gasket Supplies Co., Ltd Rm 1811, Huaxia Media Buliding No.53N. Avenue, Yantai, Shandong 264000 China <u>sales@rgs-asia.com</u>

Synthetic Fiber Beater Sheet Code: RGSB103



Dimensions

Thickness: 0.3~2.0mm 500x1500mm; 500x1000mm; 500x500mm; 500x1200mm; 1000x1500mm; 1000x1200mm;

> Copyright © 2014 RGS Rubber & Gasket Supplies Co., Ltd Rm 1811, Huaxia Media Buliding No.53N. Avenue, Yantai, Shandong 264000 China <u>sales@rgs-asia.com</u>